

# Gewebekleber



## Product description

**Characteristics:**

- Special glue for glass fabrics natural white and pre-coated
- Glue for heavy wallpapers
- Excellent adhesion
- Transparent after drying
- Airless spraying if diluted with approx. 20% water
- Easy application and fast spreading
- Very homogeneous coating
- Application with pasting machine possible, dilute JONAS Gewebekleber with approx. 15-25% water
- Long open time during application
- Easy and fast to apply big quantities of glue for very rough fabrics
- Free of solvents and emissions
- Without the addition of preservatives \*

## Material

<b>Application Area:</b>	For interior use on new and old solid undergrounds, such as mineral stucco, concrete, gypsum board (without lignin marks). Special glue for glass fleece and glass fabrics.
<b>Binding Agent:</b>	Special resin dispersion
<b>Colour:</b>	Colourless
<b>Specific gravity:</b>	1.05 g/cm <sup>3</sup>
<b>pH value:</b>	Approx. 10
<b>Diluting agent:</b>	Water
<b>Viscosity:</b>	Slightly thixotropic

# Technical data sheet

# JONAS Gewebekleber



## Application Characteristics

<b>Application:</b>	Brush / roller / spray (airless). Also recommended for use with wallpaper equipment.
<b>Underground:</b>	Needs to be clean, dry, and solid. Otherwise use JONAS Hydro-Haft-& Tiefgrund first to consolidate the underground. For underground treatment and application VOB, part C, DIN 18363 and the relevant BFS information must be observed.
<b>Coating build-up:</b>	<u>Roller:</u> without dilution. <u>Pasting machine:</u> use Gewebekleber with a dilution of approx. 15 - 25 % water. To find the ideal quantity of Gewebekleber, test with a piece of glass-fleece. <u>Airless-spray:</u> dilution: add approx. 20 % water nozzle: 0.021 – 0.027 Inch pressure: 150 – 200 bar filter: 60 Mesh
<b>Spreading rate per coating:</b>	Approx. 300 - 400 g/m <sup>2</sup> on smooth underground (if necessary test on the wall).
<b>Application temperature:</b>	At least + 5°C (Degrees Celsius) for air and underground during application and drying.
<b>Drying:</b>	The surface of the coating is dry and can be painted over after 8 - 10 hours (at a temperature of 20 °C and a relative atmospheric humidity of 65 %). High humidity, low temperatures and low air exchange extend the hardening and drying time.
<b>Cleaning of tools:</b>	Clean with water immediately after use.

## General information

<b>Storage:</b>	Cool, but not freezing.
<b>Shelf-life:</b>	Can be stored for at least 12 months after date of filling (see additional sticker) if stored properly in the unopened original packaging.
<b>Art.No. and description:</b>	42 05 001 JONAS Gewebekleber
<b>Packaging:</b>	16 kg
<b>Ingredients:</b>	Resin dispersion, cellulose derivatives, starch derivative, water, additives.
<b>Without preservatives:</b>	* o.K., i.e. we do not add any preservatives during production of this product.
<b>Safety:</b>	Please follow the instructions of the safety data sheet.
<b>Labelling:</b>	This product is not classified according to EU regulation No 1272/2008 [CLP].
<b>Waste disposal:</b>	Empty containers can be disposed for recycling. Any dried residues of material can be disposed of as construction waste or together with domestic garbage. Containers with liquid material residues must be disposed of according to local regulations. For further information, please contact your local waste authority.
<b>Advice acc. to CLP:</b>	Keep out of reach of children. Wear appropriate respiratory protection (full mask / half mask equipped with filter type A2/P2). Avoid eating, drinking and smoking during use of the product. Ensure good ventilation during and after application. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not empty into drains or water courses. Safety data sheet available on request.