according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

JONAS MIX

 Article No.:
 2222201
 Reno-Fassaden-Finish Base 1

 Print date:
 01.09.2023
 Revision date: 28.08.2023

 Version:
 10.1
 Issue date: 28.08.2023



ΕN

Page 1 / 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Article No. (manufacturer/supplier) 2222201
Trade name/designation JONAS MIX

Reno-Fassaden-Finish

Base 1

UFI: EJA3-K07C-900J-KR9N

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Coatings and paints, thinners, paint removers.

Uses advised against: when properly used - no

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

JONAS Farben GmbH

Dieselstraße 42 - 44

D-42489 Wuelfrath

Germany

Telephone: +49 2058 789 0

Telefax: +49 2058 789 55

E-mail: kontakt@jonas-farben.de

Website: www.jonas-farben.de

Department responsible for information:

E-mail (competent person): kontakt@jonas-farben.de

1.4. Emergency telephone number

Emergency telephone: +49 2058 789 0

available at office time from 07:30 a.m. to 04:00 p.m.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Skin Sens. 1 / H317 Respiratory or skin sensitisation May cause an allergic skin reaction.

Aquatic Chronic 3 / H412 Hazardous to the aquatic environment Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Warning

Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.
P261 When spraying, use combination filter A2 / P2.

P273 Avoid release to the environment.

P280 Wear protective gloves and eye/face protection.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents / container in accordance with local regulations.

Hazard components for labelling

2-methyl-2H-isothiazol-3-one 1,2-benzisothiazol-3(2H)-one 2-octyl-2H-isothiazol-3-one

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

JONAS MIX

 Article No.:
 2222201
 Reno-Fassaden-Finish Base 1

 Print date:
 01.09.2023
 Revision date: 28.08.2023

 Version:
 10.1
 Issue date: 28.08.2023



EN Page 2 / 8

4,5-Dichloro-2-octyl-2H-isothiazol-3-one

Supplemental hazard information

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

EUH210 Safety data sheet available on request.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description Dispersion paint, algicide and fungicide

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No.	REACH No. Designation	woight %
Index No.	classification: // Remark	weight-%
236-675-5		
13463-67-7	titanium dioxide	10 - 20
022-006-00-2	Carc. 2 H351	
220-120-9		
2634-33-5	1,2-benzisothiazol-3(2H)-one	< 0,1
613-088-00-6	Acute Tox. 4 H302 / Acute Tox. 2 H330 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 / Skin Sens. 1 H317 / Aquatic Acute 1 H400 (M = 1) / Aquatic Chronic 1 H410 (M = 1)	
220-239-6		
2682-20-4	2-methyl-2H-isothiazol-3-one Acute Tox. 3 H301 / Acute Tox. 3 H311 / Acute Tox. 2 H330 / Skin Corr. 1B H314 / Eye Dam. 1 H318 / Skin Sens. 1A H317 / Aquatic Acute 1 H400 (M = 10) / Aquatic Chronic 1 H410 (M = 1)	< 0,1
212-950-5		
886-50-0	Terbutryn Acute Tox. 4 H302 / Skin Sens. 1B H317 / Aquatic Acute 1 H400 (M = 100) / Aquatic Chronic 1 H410 (M = 100)	< 0,1
247-761-7		
26530-20-1 613-112-00-5	2-octyl-2H-isothiazol-3-one Acute Tox. 3 H301 / Acute Tox. 3 H311 / Acute Tox. 2 H330 / Skin Corr. 1 H314 / Eye Dam. 1 H318 / Skin Sens. 1A H317 / Aquatic Acute 1 H400 (M = 100) / Aquatic Chronic 1 H410 (M = 100)	< 0,1
264-843-8		
64359-81-5	4,5-Dichloro-2-octyl-2H-isothiazol-3-one Acute Tox. 4 H302 / Acute Tox. 2 H330 / Skin Corr. 1 H314 / Eye Dam. 1 H318 / Skin Sens. 1A H317 / Aquatic Acute 1 H400 (M = 100) / Aquatic Chronic 1 H410 (M = 100)	< 0,1
614-170-4		
67923-10-8	Skin Irrit. 2 H315 / Eye Irrit. 2 H319	1 - 2,5

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



Article No.: 2222201 Reno-Fassaden-Finish Base 1
Print date: 01.09.2023 Revision date: 28.08.2023
Version: 10.1 Issue date: 28.08.2023



EN Page 3 / 8

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

Additional information

The product itself does not burn.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

JONAS MIX

 Article No.:
 2222201
 Reno-Fassaden-Finish Base 1

 Print date:
 01.09.2023
 Revision date: 28.08.2023

 Version:
 10.1
 Issue date: 28.08.2023



EN Page 4 / 8

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

titanium dioxide

Index No. 022-006-00-2 / EC No. 236-675-5 / CAS No. 13463-67-7

WEL, TWA: 10 mg/m3 Remark: (inhalable fraction) WEL, TWA: 4 mg/m3 Remark: (respirable fraction)

Additional information

TWA: Long-term occupational exposure limit value STEL: short-term occupational exposure limit value

Ceiling: peak limitation

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibres (cotton) or heat resistant synthetic fibres.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state: Liquid
Appearance: viskos
Colour: white

Odour: low odor
pH at 20 °C: 8 - 8,5

Melting point/freezing point not determined Initial boiling point and boiling range: not determined Flash point: not applicable

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

JONAS MIX

 Article No.:
 2222201
 Reno-Fassaden-Finish Base 1

 Print date:
 01.09.2023
 Revision date: 28.08.2023

 Version:
 10.1
 Issue date: 28.08.2023



EN Page 5 / 8

Explosion limits (LEL, UEL)
Lower explosion limit:

0,6

Dipropylene glycol n-butyl ether

Upper explosion limit:

20,4

Dipropylene glycol n-butyl ether

Vapour pressure at 20 °C: 0,0018 mbar
Relative vapour density not determined

Density and/or relative density:

1,57 +/- 0,05 g/cm³

Solubility(ies):

Water solubility at 20 °C: completely miscible

Partition coefficient n-octanol /water (log P

D/W):

Remark: not determined

Auto-ignition temperature:

Remark: No data available

Decomposition temperature:

Remark: No data available

Dynamic viscosity (20°C): 14500 mPa* s Cinematic viscosity (40°C): 9235,67 mm²/s

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

titanium dioxide

Carcinogenicity

Contains less than 1 % titanium dioxide particles with an aerodynamic diameter = 10 µm.

STOT-single exposure; STOT-repeated exposure

Based on available data, the classification criteria are not met.

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

JONAS MIX

 Article No.:
 2222201
 Reno-Fassaden-Finish Base 1

 Print date:
 01.09.2023
 Revision date: 28.08.2023

 Version:
 10.1
 Issue date: 28.08.2023



EN Page 6 / 8

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and has not been classified.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself.

Do not allow to enter into surface water or drains.

12.1. Toxicity

Based on available data, the classification criteria are not met.

Long-term Ecotoxicity

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111* Waste paint and varnish containing organic solvents or other dangerous substances

Appropriate disposal / Package

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste. A 150110packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

No dangerous good in sense of this transport regulation.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



Article No.: 2222201 Reno-Fassaden-Finish Base 1
Print date: 01.09.2023 Revision date: 28.08.2023
Version: 10.1 Issue date: 28.08.2023



EN Page 7 / 8

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

Land transport (ADR/RID) not applicable

Marine pollutant not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code

Sea transport (IMDG)

EmS-No. not applicable

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EU) No. 528/2012 on biocides

biocide, active substance

5-chloro-2-methyl-2H-isothiazol-3-one

1,2-benzisothiazol-3(2H)-one

2-octyl-2H-isothiazol-3-one

2-methyl-2H-isothiazol-3-one

3-iodo-2-propinyl butylcarbamate

4,5-Dichloro-2-octyl-2H-isothiazol-3-one

Terbutryn

Use

Main group 2: Preservatives

Product-type 7: Film preservatives

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 40

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/c); VOC limit value: 40 g/l

Maximum VOC content of the product in a ready to use condition (in g/L): 40

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Full text of classification in section 3:

Carc. 2 / H351 Carcinogenicity

Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



ΕN

Very toxic to aquatic organisms.

JONAS MIX

Reno-Fassaden-Finish Base 1 Article No.: 2222201 Revision date: 28.08.2023 Issue date: 28.08.2023 Print date: 01.09.2023 Page 8 / 8 Version:

Acute Tox. 4 / H302 Harmful if swallowed. Acute toxicity (oral) Acute Tox. 2 / H330 Acute toxicity (inhalative) Fatal if inhaled Skin Irrit. 2 / H315 Skin corrosion/irritation Causes skin irritation. Eve Dam. 1 / H318 Serious eve damage/eve irritation Causes serious eye damage. Respiratory or skin sensitisation May cause an allergic skin reaction. Skin Sens. 1 / H317

Very toxic to aquatic life with long lasting Aquatic Chronic 1 / H410 Hazardous to the aquatic environment

effects.

Toxic if swallowed. Acute Tox. 3 / H301 Acute toxicity (oral) Acute Tox. 3 / H311 Acute toxicity (dermal) Toxic in contact with skin.

Hazardous to the aquatic environment

Skin Corr. 1B / H314 Skin corrosion/irritation Causes severe skin burns and eve damage.

Skin Sens. 1A / H317 Respiratory or skin sensitisation May cause an allergic skin reaction. Skin Sens. 1B / H317 Respiratory or skin sensitisation May cause an allergic skin reaction.

Skin Corr. 1 / H314 Skin corrosion/irritation Causes severe skin burns and eye damage.

Eye Irrit. 2 / H319 Serious eye damage/eye irritation Causes serious eye irritation.

Abbreviations and acronyms

Aquatic Acute 1 / H400

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL Occupational Exposure Limit Value

Biological Limit Value **BLV** CAS Chemical Abstracts Service

Classification, Labelling and Packaging CLP CMR Carcinogenic, Mutagenic and Reprotoxic

German Institute for Standardization / German industrial standard DIN

DNEL Derived No-Effect Level

EAKV European Waste Catalogue Directive

EC Effective Concentration EC **European Community** ΕN European Standard

IATA-DGR International Air Transport Association - Dangerous Goods Regulations

IBC Code International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk ICAO-TI International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous

Goods by Air

IMDG Code International Maritime Code for Dangerous Goods ISO International Organization for Standardization

LC Lethal Concentration

LD Lethal Dose

MARPOL Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD Organisation for Economic Cooperation and Development

persistent, bioaccumulative, toxic **PBT PNEC** Predicted No Effect Concentration

Registration, Evaluation, Authorisation and Restriction of Chemicals **REACH**

IMDG Code International Maritime Code for Dangerous Goods ISO International Organization for Standardization

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1.It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

^{*} Data changed compared with the previous version

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

JONAS MIX

Article No.: 2222401 Reno-Fassaden-Finish Base 3
Print date: 01.09.2023 Revision date: 28.08.2023
Version: 7.1 Issue date: 28.08.2023



ΕN

Page 1 / 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Article No. (manufacturer/supplier) 2222401
Trade name/designation JONAS MIX

Reno-Fassaden-Finish

Base 3

UFI: EXC3-P08Q-600G-56MP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Coatings and paints, thinners, paint removers.

Uses advised against: when properly used - no

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

JONAS Farben GmbH

Dieselstraße 42 - 44

D-42489 Wuelfrath

Germany

Telephone: +49 2058 789 0

Telefax: +49 2058 789 55

E-mail: kontakt@jonas-farben.de

Website: www.jonas-farben.de

Department responsible for information:

E-mail (competent person): kontakt@jonas-farben.de

1.4. Emergency telephone number

Emergency telephone: +49 2058 789 0

available at office time from 07:30 a.m. to 04:00 p.m.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Skin Sens. 1 / H317 Respiratory or skin sensitisation May cause an allergic skin reaction.

Aquatic Chronic 3 / H412 Hazardous to the aquatic environment Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Warning

Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.
P261 When spraying, use combination filter A2 / P2.

P273 Avoid release to the environment.

P280 Wear protective gloves and eye/face protection.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P362 + P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents / container in accordance with local regulations.

Hazard components for labelling

2-methyl-2H-isothiazol-3-one 1,2-benzisothiazol-3(2H)-one 2-octyl-2H-isothiazol-3-one

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

JONAS MIX

Article No.: 2222401 Print date: 01.09.2023 Version: 7.1 Reno-Fassaden-Finish Base 3 Revision date: 28.08.2023 Issue date: 28.08.2023



EN Page 2 / 8

4,5-Dichloro-2-octyl-2H-isothiazol-3-one

Supplemental hazard information

not applicable

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description Dispersion paint, algicide and fungicide

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No. Designation classification: // Remark	weight-%
220-120-9 2634-33-5 613-088-00-6	1,2-benzisothiazol-3(2H)-one Acute Tox. 4 H302 / Acute Tox. 2 H330 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 / Skin Sens. 1 H317 / Aquatic Acute 1 H400 (M = 1) / Aquatic Chronic 1 H410 (M = 1)	< 0,1
220-239-6 2682-20-4	2-methyl-2H-isothiazol-3-one Acute Tox. 3 H301 / Acute Tox. 3 H311 / Acute Tox. 2 H330 / Skin Corr. 1B H314 / Eye Dam. 1 H318 / Skin Sens. 1A H317 / Aquatic Acute 1 H400 (M = 10) / Aquatic Chronic 1 H410 (M = 1)	< 0,1
212-950-5 886-50-0	Terbutryn Acute Tox. 4 H302 / Skin Sens. 1B H317 / Aquatic Acute 1 H400 (M = 100) / Aquatic Chronic 1 H410 (M = 100)	< 0,1
247-761-7 26530-20-1 613-112-00-5	2-octyl-2H-isothiazol-3-one Acute Tox. 3 H301 / Acute Tox. 3 H311 / Acute Tox. 2 H330 / Skin Corr. 1 H314 / Eye Dam. 1 H318 / Skin Sens. 1A H317 / Aquatic Acute 1 H400 (M = 100) / Aquatic Chronic 1 H410 (M = 100)	< 0,1
264-843-8 64359-81-5	4,5-Dichloro-2-octyl-2H-isothiazol-3-one Acute Tox. 4 H302 / Acute Tox. 2 H330 / Skin Corr. 1 H314 / Eye Dam. 1 H318 / Skin Sens. 1A H317 / Aquatic Acute 1 H400 (M = 100) / Aquatic Chronic 1 H410 (M = 100)	< 0,1
614-170-4 67923-10-8	Skin Irrit. 2 H315 / Eye Irrit. 2 H319	1 - 2,5

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

JONAS MIX

Article No.: 2222401 Reno-Fassaden-Finish Base 3
Print date: 01.09.2023 Revision date: 28.08.2023
Version: 7.1 Issue date: 28.08.2023



EN Page 3 / 8

medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid. decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

Additional information

The product itself does not burn.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

JONAS MIX

Article No.: 2222401 Reno-Fassaden-Finish Base 3
Print date: 01.09.2023 Revision date: 28.08.2023
Version: 7.1 Issue date: 28.08.2023



EN Page 4 / 8

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

not applicable

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibres (cotton) or heat resistant synthetic fibres.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state:

Appearance:

Colour:

Odour:

Diw odor

pH at 20 °C:

Liquid

viskos

white

low odor

8 - 8,5

Melting point/freezing point not determined Initial boiling point and boiling range: not determined Flash point: not applicable

Explosion limits (LEL, UEL)

Lower explosion limit: 0,6

Dipropylene glycol n-butyl ether

Upper explosion limit: 20,4

Dipropylene glycol n-butyl ether

Vapour pressure at 20 °C: 0,0012 mbar
Relative vapour density not determined

Density and/or relative density:

1,37 +/- 0,05 g/cm³

Solubility(ies):

Water solubility at 20 °C: completely miscible

Partition coefficient n-octanol /water (log P

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



 Article No.:
 2222401
 Reno-Fassaden-Finish Base 3

 Print date:
 01.09.2023
 Revision date: 28.08.2023

 Version:
 7.1
 Issue date: 28.08.2023



EN Page 5 / 8

O/W):

Remark: not determined

Auto-ignition temperature:

Remark: No data available

Decomposition temperature:

Remark: No data available

Dynamic viscosity (20°C): 13000 mPa* s Cinematic viscosity (40°C): 9489,05 mm²/s

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and has not been classified.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself.

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

JONAS MIX

 Article No.:
 2222401
 Reno-Fassaden-Finish Base 3

 Print date:
 01.09.2023
 Revision date: 28.08.2023

 Version:
 7.1
 Issue date: 28.08.2023



EN Page 6 / 8

Do not allow to enter into surface water or drains.

12.1. Toxicity

Based on available data, the classification criteria are not met.

Long-term Ecotoxicity

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111*

Waste paint and varnish containing organic solvents or other dangerous substances

Appropriate disposal / Package

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste. A 150110packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

No dangerous good in sense of this transport regulation.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

Land transport (ADR/RID) not applicable

Marine pollutant not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

JONAS MIX

Article No.: 2222401 Reno-Fassaden-Finish Base 3
Print date: 01.09.2023 Revision date: 28.08.2023
Version: 7.1 Issue date: 28.08.2023



EN Page 7 / 8

Land transport (ADR/RID)

Tunnel restriction code

Sea transport (IMDG)

EmS-No. not applicable

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EU) No. 528/2012 on biocides

biocide, active substance

5-chloro-2-methyl-2H-isothiazol-3-one

1,2-benzisothiazol-3(2H)-one

2-octyl-2H-isothiazol-3-one

2-methyl-2H-isothiazol-3-one

3-iodo-2-propinyl butylcarbamate

4,5-Dichloro-2-octyl-2H-isothiazol-3-one

Terbutryn

Use

Main group 2: Preservatives

Product-type 7: Film preservatives

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 40

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/c); VOC limit value: 40 g/l

Maximum VOC content of the product in a ready to use condition (in g/L): 40

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Full text of classification in section 3:

Acute Tox. 4 / H302 Acute toxicity (oral) Harmful if swallowed.

Acute Tox. 2 / H330 Acute toxicity (inhalative) Fatal if inhaled.

Skin Irrit. 2 / H315 Skin corrosion/irritation Causes skin irritation.

Eye Dam. 1 / H318 Serious eye damage/eye irritation Causes serious eye damage.

Skin Sens. 1 / H317 Respiratory or skin sensitisation May cause an allergic skin reaction.

Aquatic Acute 1 / H400 Hazardous to the aquatic environment Very toxic to aquatic organisms.

Aquatic Chronic 1 / H410 Hazardous to the aquatic environment Very toxic to aquatic life with long lasting

effects.

Acute Tox. 3 / H301 Acute toxicity (oral) Toxic if swallowed.

Acute Tox. 3 / H311 Acute toxicity (dermal) Toxic in contact with skin.

Skin Corr. 1B / H314 Skin corrosion/irritation Causes severe skin burns and eye damage.

Skin Sens. 1A / H317 Respiratory or skin sensitisation May cause an allergic skin reaction.

Skin Sens. 1B / H317 Respiratory or skin sensitisation May cause an allergic skin reaction.

Skin Corr. 1 / H314 Skin corrosion/irritation Causes severe skin burns and eye damage. Eye Irrit. 2 / H319 Serious eye damage/eye irritation Causes serious eye irritation.

Abbreviations and acronyms

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL Occupational Exposure Limit Value

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



ΕN

Page 8 / 8

JONAS MIX

Article No.: 2222401 Reno-Fassaden-Finish Base 3
Print date: 01.09.2023 Revision date: 28.08.2023
Version: 7.1 Issue date: 28.08.2023

BLV Biological Limit Value CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging CMR Carcinogenic, Mutagenic and Reprotoxic

DIN German Institute for Standardization / German industrial standard

DNEL Derived No-Effect Level

EAKV European Waste Catalogue Directive

EC Effective Concentration
EC European Community
EN European Standard

IATA-DGR International Air Transport Association – Dangerous Goods Regulations

IBC Code International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk ICAO-TI International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous

Goods by Air

IMDG Code International Maritime Code for Dangerous Goods ISO International Organization for Standardization

LC Lethal Concentration

LD Lethal Dose

MARPOL Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD Organisation for Economic Cooperation and Development

PBT persistent, bioaccumulative, toxic PNEC Predicted No Effect Concentration

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

IMDG Code International Maritime Code for Dangerous Goods ISO International Organization for Standardization

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

^{*} Data changed compared with the previous version