# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

**JONAS** 

Article No.: 1800001 Silikat-Fassadenfarbe
Print date: 19.05.2022 Revision date: 19.10.2021
Version: 9.1 Issue date: 19.10.2021



Page 1 / 7

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Article No. (manufacturer/supplier) 1800001 Trade name/designation JONAS

Silikat-Fassadenfarbe

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture:

Coatings and paints, thinners, paint removers.

when properly used - no

## 1.3. Details of the supplier of the safety data sheet

#### supplier (manufacturer/importer/downstream user/distributor)

JONAS Farben GmbH

Dieselstraße 42 - 44

D-42489 Wuelfrath

Germany

Telephone: +49 2058 789 0

Telefax: +49 2058 789 55

E-mail: kontakt@jonas-farben.de

Website: www.ionas-farben.de

Department responsible for information:

E-mail (competent person): kontakt@jonas-farben.de

1.4. Emergency telephone number

Emergency telephone: +49 2058 789 0

available at office time from 07:30 a.m. to 04:00 p.m.

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

# Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

#### 2.2. Label elements

# Labelling according to Regulation (EC) No. 1272/2008 [CLP]

**Hazard pictograms** 

**Hazard statements** 

not applicable

**Precautionary statements** 

not applicable

Hazard components for labelling

not applicable

Supplemental hazard information

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

EUH210 Safety data sheet available on request.

2.3. Other hazards

No information available.

## **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

**Description** Dispersion silicate paint

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. REACH No. CAS No. Designation

Index No. classification: // Remark

weight-%

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



**JONAS** 

Article No.: 1800001 Silikat-Fassadenfarbe
Print date: 19.05.2022 Revision date: 19.10.2021
Version: 9.1 Issue date: 19.10.2021

EN Page 2 / 7

236-675-5 13463-67-7 titanium dioxide 10 - 20 022-006-00-2 Carc. 2 H351

215-199-1

1312-76-1 Silicic acid, potassium salt 2,5 - 5

Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / STOT SE 3 H335

#### **Additional information**

Full text of classification: see section 16

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

## Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

# 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

#### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

# Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

# Unsuitable extinguishing media

strong water jet

## 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

#### 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

#### Additional information

The product itself does not burn.

## **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

#### 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

JONAS

 Article No.:
 1800001
 Silikat-Fassadenfarbe

 Print date:
 19.05.2022
 Revision date: 19.10.2021

 Version:
 9.1
 Issue date: 19.10.2021



EN Page 3 / 7

#### 6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

## Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

## 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

## Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

## Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

## 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

# Occupational exposure limit values

titanium dioxide

Index No. 022-006-00-2 / EC No. 236-675-5 / CAS No. 13463-67-7

WEL, TWA: 4 mg/m3 Remark: (respirable fraction) WEL, TWA: 10 mg/m3 Remark: (inhalable fraction)

## Additional information

TWA: Long-term occupational exposure limit value STEL: short-term occupational exposure limit value

Ceiling: peak limitation

## 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

## Personal protection equipment

## Respiratory protection

Do not breathe spray mist or vapor / aerosol. Do not wear respiratory protection. Full and half mask with matching filter (combination filter type A2 / P2).

## **Hand protection**

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

# Eye/face protection

Wear closely fitting protective glasses in case of splashes.

## **Body protection**

Wear antistatic clothing of natural fibres (cotton) or heat resistant synthetic fibres.

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

**JONAS** 

 Article No.:
 1800001
 Silikat-Fassadenfarbe

 Print date:
 19.05.2022
 Revision date: 19.10.2021

 Version:
 9.1
 Issue date: 19.10.2021



EN Page 4 / 7

#### Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

## **Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Appearance:

Physical state: Liquid white

Odour: low odor

Odour threshold: not determined

pH at 20 °C: 10,5 - 11,5 / 100,0 weight-%

Melting point/freezing point: not determined

Initial boiling point and boiling range: 100 °C

Source: water

Flash point: not applicable Evaporation rate: not applicable

flammability

Burning time: not applicable

Upper/lower flammability or explosive limits:

Lower explosion limit:

Upper explosion limit:

Vapour pressure at 20 °C:

Napour density:

not applicable

not applicable

not determined

Relative density:

Density at 20 °C: 1,48 +/- 0,05 g/cm<sup>3</sup>

Solubility(ies):

Water solubility at 20 °C: completely miscible

Partition coefficient: n-octanol/water: see section 12
Auto-ignition temperature: not applicable
Decomposition temperature: not applicable
Viscosity at 20 °C: 14500 mPa\*s
Explosive properties: not determined
Oxidising properties: not determined

9.2. Other information

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

No information available.

#### 10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

#### 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

#### 10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

#### 10.5. Incompatible materials

not applicable

# 10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide,

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

**JONAS** 

Article No.: 1800001 Silikat-Fassadenfarbe
Print date: 19.05.2022 Revision date: 19.10.2021
Version: 9.1 Issue date: 19.10.2021



EN Page 5 / 7

smoke, nitrogen oxides.

# **SECTION 11: Toxicological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

No data on preparation itself available.

#### 11.1. Information on toxicological effects

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

## Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

## CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

#### STOT-single exposure; STOT-repeated exposure

Based on available data, the classification criteria are not met.

## **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### Practical experience/human evidence

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

#### **Overall Assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

#### Remark

There is no information available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and has not been classified.

# **SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

#### 12.1. Toxicity

Based on available data, the classification criteria are not met.

## Long-term Ecotoxicity

Toxicological data are not available.

## 12.2. Persistence and degradability

Toxicological data are not available.

## 12.3. Bioaccumulative potential

Toxicological data are not available.

# Bioconcentration factor (BCF)

Toxicological data are not available.

# 12.4. Mobility in soil

Toxicological data are not available.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

No information available.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



Article No.: 1800001 Silikat-Fassadenfarbe
Print date: 19.05.2022 Revision date: 19.10.2021
Version: 9.1 Issue date: 19.10.2021



EN Page 6 / 7

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

#### List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 08 01 11

# Appropriate disposal / Package

#### Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste. A 150110 packaging containing residues of or contaminated by dangerous substances

#### **SECTION 14: Transport information**

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

No dangerous good in sense of this transport regulation.

14.1. UN number

not applicable

14.2. UN proper shipping name

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

Land transport (ADR/RID) not applicable

Marine pollutant not applicable

#### 14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

#### **Further information**

## Land transport (ADR/RID)

tunnel restriction code

Sea transport (IMDG)

EmS-No. not applicable

# 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# **EU** legislation

#### Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 1

## Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC product category: (Cat. A/c); VOC limit value: 40 g/l

Maximum VOC content (g/L) of the product in a ready to use condition: 1

# **National regulations**

## Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

#### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

# **SECTION 16: Other information**

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

**JONAS** 

Article No.: 1800001 Silikat-Fassadenfarbe
Print date: 19.05.2022 Revision date: 19.10.2021
Version: 9.1 Issue date: 19.10.2021



EN Page 7 / 7

#### Full text of classification in section 3:

Carc. 2 / H351 Carcinogenicity Suspected of causing cancer if inhaled.

Skin Irrit. 2 / H315 Skin corrosion/irritation Causes skin irritation.

Eye Irrit. 2 / H319 Serious eye damage/eye irritation Causes serious eye irritation.

STOT SE 3 / H335 STOT-single exposure May cause respiratory irritation.

## Abbreviations and acronyms

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL Occupational Exposure Limit Value

BLV Biological Limit Value CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging CMR Carcinogenic, Mutagenic and Reprotoxic

DIN German Institute for Standardization / German industrial standard

DNEL Derived No-Effect Level

EAKV European Waste Catalogue Directive

EC Effective Concentration
EC European Community
EN European Standard

IATA-DGR International Air Transport Association – Dangerous Goods Regulations

IBC Code International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk ICAO-TI International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous

Goods by Air

IMDG Code International Maritime Code for Dangerous Goods ISO International Organization for Standardization

LC Lethal Concentration

LD Lethal Dose

MARPOL Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD Organisation for Economic Cooperation and Development

PBT persistent, bioaccumulative, toxic PNEC Predicted No Effect Concentration

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

IMDG Code International Maritime Code for Dangerous Goods ISO International Organization for Standardization

VOC Volatile Organic Compounds

vPvB very persistent and very bioaccumulative

#### **Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

<sup>\*</sup> Data changed compared with the previous version