

Assortment



## Paints are our passion

We think in colours for over 85 years. As an industrial company, we are particularly responsible for the world of tomorrow. For this reason, we constantly improve our products, save resources and manufacture eco-friendly and sustainable.

We listen and therefore know what our customers need and desire. Every day, we realize this principle with high commitment – from order to just-in-time delivery. Because we love, what we do.

# Table of contents

<b>Paints for interior use wet scrub resistance class 1</b>	<b>4 – 7</b>
<b>Paints for interior use wet scrub resistance class 2</b>	<b>7 – 9</b>
<b>Paints for interior use wet scrub resistance class 3 + 4</b>	<b>10 – 11</b>
<b>Paints for exterior use</b>	<b>12 – 15</b>
<b>Tinting paints</b>	<b>15</b>
<b>Primers</b>	<b>16 – 20</b>
<b>Comparison of primers</b>	<b>21</b>
<b>Glue for wallpapers</b>	<b>22 – 23</b>
<b>Texturing coatings</b>	<b>24 – 27</b>
<b>MIX products</b>	<b>28 – 33</b>
<b>Proofs / Certificates</b>	<b>34 – 37</b>
<b>Pictograms</b>	<b>38</b>
<b>Guideline for airless-spraying</b>	<b>39</b>



Paints for interior use

## Wet scrub resistance class 1



### Doppeldecker

High quality single-coat paint for interior use. Matt finish. High whiteness combined with a very good hiding power. Excellent application properties. The product conserves the structure and gives a durable surface. Resistant to disinfectants. Certified and monitored by TÜV SÜD with respect to emissions. Free of solvents and harmful emissions. Without the addition of preservatives.

#### DIN EN 13300:

Contrast ratio: hiding power H<sub>10</sub>-class 1 at a spreading rate of 125 ml/m<sup>2</sup>

Wet scrub resistance: R-class 1

Gloss level: G4 dull matt

colour: white



spreading rate / m<sup>2</sup>  
per coating

approx. 150 ml

packaging

12.5 l  
5 l

bucket/Euro  
pallet

32  
72



### Silikon-Innenfarbe

Non-glossy silicone paint for interior use. With very good hiding power and excellent application properties. Offering a long open time it is particularly suitable for large and smooth walls and ceilings. Free of solvents and harmful emissions. Without the addition of preservatives.

#### DIN EN 13300:

Contrast ratio: hiding power H<sub>10</sub>-class 1 at a spreading rate of 125 ml/m<sup>2</sup>

Wet scrub resistance: R-class 1

Gloss level: G4 dull matt

colour: white



spreading rate / m<sup>2</sup>  
per coating

approx. 150 ml

12.5 l

32



### Ultramatt premium

Premium quality non-glossy latex paint for interior use. For all common substrates. With excellent application properties. Retaining the structure, hard-wearing and scrub resistant. Extremely long open time, low spattering. Free of solvents and harmful emissions. Without the addition of preservatives.

#### DIN EN 13300:

Contrast ratio: hiding power H<sub>10</sub>-class 1 at a spreading rate of 165 ml/m<sup>2</sup>

Wet scrub resistance: R-class 1

Gloss level: G4 dull matt

colour: white



spreading rate / m<sup>2</sup>  
per coating

approx. 150 ml

12.5 l  
5 l

32  
72



### Samtmatt premium

Premium quality hard-wearing silk-matt latex paint for interior use. Enhances the writing resistance (finish), especially for dark colours. Good hiding power as well as a very fine and even structure combined with excellent application properties guarantee an perfect surface. Free of solvents and harmful emissions. Without the addition of preservatives.

#### DIN EN 13300:

Contrast ratio: hiding power H<sub>10</sub>-class 1 at a spreading rate of 165 ml/m<sup>2</sup>

Wet scrub resistance: R-class 1

Gloss level: G2b medium gloss

colour: white



spreading rate / m<sup>2</sup>  
per coating

approx. 150 ml

12.5 l  
5 l

32  
72

Wet scrub resistance class 1		spreading rate / m <sup>2</sup> per coating	packaging	bucket/Euro pallet
	<b>Seidenglanz premium</b> Premium quality silk-gloss latex paint for exterior and interior use. Retaining the structure and hard-wearing. UV-resistant with stable gloss. Resistant to disinfectants. Weatherproof. Free of solvents and harmful emissions. Without the addition of preservatives. <b>DIN EN 13300:</b> Contrast ratio: hiding power H <sub>10</sub> -class 1 at a spreading rate of 165 ml/m <sup>2</sup> Wet scrub resistance: R-class 1 Gloss level: G2b medium gloss <b>colour:</b> white	approx. 140 ml	12.5 l 5 l	32 72
				
	<b>Hochglanz premium</b> Premium quality high-gloss latex paint for exterior and interior use. With very good hiding power, very durable and hard-wearing. Best application properties and an excellent surface finish. UV-resistant with stable gloss. Resistant to disinfectants. Free of solvents and harmful emissions. Without the addition of preservatives. <b>DIN EN 13300:</b> Contrast ratio: hiding power H <sub>10</sub> -class 1 at a spreading rate of 125 ml/m <sup>2</sup> Wet scrub resistance: R-class 1 Gloss level: G2a medium gloss <b>colour:</b> white	approx. 130 ml	12.5 l 5 l	32 72
				
	<b>Seidenlatex</b> Silk-gloss latex paint of high quality, for exterior and interior use. Good surface finish with accentuating effects on structured wallpapers or glass fibres. UV-resistant with stable gloss. Good hiding power, low smell and environmentally friendly. Resistant to disinfectants. Free of solvents and harmful emissions. Without the addition of preservatives. <b>DIN EN 13300:</b> Contrast ratio: hiding power H <sub>10</sub> -class 1 at a spreading rate of 165 ml/m <sup>2</sup> Wet scrub resistance: R-class 1 Gloss level: G2b medium gloss <b>colour:</b> white/off-white	approx. 150 ml	12.5 l 5 l 2.5 l	32 72 120
				
	<b>Sol-Silikat-Innenfarbe</b> Highly diffusible silicate paint according to DIN 18363, for interior use. Snow-white with very good hiding power. Sol-silicate offers outstanding processing properties and high durability. Suitable for mineral substrates and for reworking old, matt dispersion and silicone-resin based paints. Resistant to disinfectants. Free of plasticizers and fogging active substances. Free of solvents and harmful emissions. Without the addition of preservatives. <b>DIN EN 13300:</b> Contrast ratio: hiding power H <sub>10</sub> -class 1 at a spreading rate of 140 ml/m <sup>2</sup> Wet scrub resistance: R-class 1 Gloss level: G4 dull matt <b>colour:</b> white	approx. 150 ml	12.5 l 5 l	32 72
				



## Wet scrub resistance class 1



### Dura-In

Premium quality paint for interior use, especially for surfaces which are under high mechanical stress. Any writing effects can be removed easily and the paint has a low tendency for soiling. It offers good hiding power and high whiteness. Together with the very fine and even texture this guarantees a perfect surface. A long open time and excellent application properties make it easy to use. Resistant to disinfectants.

Free of solvents and harmful emissions.

#### DIN EN 13300:

Contrast ratio: hiding power H<sub>10</sub>-class 2 at a spreading rate of 140 ml/m<sup>2</sup>

Wet scrub resistance: R-class 1

Gloss level: G4 dull matt

colour: white



spreading rate / m<sup>2</sup>  
per coating

approx. 150 ml

packaging

12.5 l  
5 l

bucket/Euro  
pallet

32  
72

## Wet scrub resistance class 2



### First Class

Single coat paint with very good hiding power and a very fine surface finish. For luxurios matt and smooth surfaces. Particularly suitable for adverse lighting conditions (such as indirect light reflections). With excellent application properties and long open time. Low consumption and good ability to conserve the structure of the substrate. Free of solvents and harmful emissions. Without the addition of preservatives.

#### DIN EN 13300:

Contrast ratio: hiding power H<sub>10</sub>-class 1 at a spreading rate of 125 ml/m<sup>2</sup>

Wet scrub resistance: R-class 2

Gloss level: G4 dull matt

colour: white



approx. 150 ml

12.5 l  
10 l  
5 l  
2.5 l

32  
40  
72  
120



### Rapidweiß

Single coating dispersion paint with very good hiding power for interior use. Slightly filling, with excellent application properties and with high efficiency. Free of solvents and harmful emissions. Without the addition of preservatives.

#### DIN EN 13300:

Contrast ratio: hiding power H<sub>10</sub>-class 1 at a spreading rate of 125 ml/m<sup>2</sup>

Wet scrub resistance: R-class 2

Gloss level: G4 dull matt

colour: white



approx. 150 ml

12.5 l  
5 l

32  
72



### Malerweiß *extra*

Dispersion paint for interior use with very high degree of whiteness and with very good hiding power. Slightly filling, with excellent application properties and long open time. Free of solvents and harmful emissions. Without the addition of preservatives.

#### DIN EN 13300:

Contrast ratio: hiding power H<sub>10</sub>-class 1 at a spreading rate of 125 ml/m<sup>2</sup>

Wet scrub resistance: R-class 2

Gloss level: G4 dull matt

colour: white



approx. 150 ml

12.5 l

32



## Over 250 labels trust our quality









Whoever decides to work with JONAS Farben for their private label wins a reliable partner, delivering class-leading products which meet all sustainability requirements demanded by customers.

The 'Blue Angel', 'Ecolabel' or 'TÜV-label', many JONAS products are certified. Independent inspections by neutral third parties confirm consistent, eco-friendly as well as practical product quality.

Create your own label. We jointly develop your own private label concept as well as a product design that is unique to the market. By corresponding branding, we specifically and actively get your private label off the ground.

Our product range is oriented by the needs of paint wholesalers and professional painting businesses. We listen to feedback and therefore know exactly what our customers need and desire.



Wet scrub resistance class 2		spreading rate / m <sup>2</sup> per coating	packaging	bucket/Euro pallet
	<b>Mattlatex</b> Matt latex paint for high quality demands, very good hiding power. Good surface finish. Durable and hard-wearing, with very low consumption. Resistant to disinfectants. Free of solvents and harmful emissions. Without the addition of preservatives. <b>DIN EN 13300:</b> Contrast ratio: hiding power H <sub>10</sub> -class 1 at a spreading rate of 165 ml/m <sup>2</sup> Wet scrub resistance: R-class 2 Gloss level: G4 dull matt <b>colour:</b> white	approx. 150 ml	12.5 l 5 l	32 72
				
	<b>Bio-Innensilikat</b> Silicate paint for interior use, highly diffusible, according to DIN 18363, snow-white with high durability. Free of plasticizers and fogging-active substances. Free of solvents and harmful emissions. Without the addition of preservatives. <b>DIN EN 13300:</b> Contrast ratio: hiding power H <sub>10</sub> -class 1 at a spreading rate of 140 ml/m <sup>2</sup> Wet scrub resistance: R-class 2 Gloss level: G4 dull matt <b>colour:</b> white	approx. 150 ml	12.5 l 5 l	32 72
	<i>* „JONAS Bio-Innensilikat“ is by the Blue Angel certified under the name „JONAS Mineral-Innensilikat“</i> 			
	<b>Iso-Matt-Aqua</b> Water-based isolating paint for interior use, no smell. Matt and tension-free, for isolating nicotine, soot and dried water stains. Free of solvents and harmful emissions. <b>DIN EN 13300:</b> Contrast ratio: hiding power H <sub>10</sub> -class 1 at a spreading rate of 140 ml/m <sup>2</sup> Wet scrub resistance: R-class 2 Gloss level: G4 dull matt <b>colour:</b> white	approx. 150-180 ml	12.5 l 5 l	32 72
				
	<b>Renovierfarbe</b> Solvent-based paint with matt finish for interior use with low tension. Perfectly suited for isolating nicotine, lignin, soot and dried water stains. Free of aromatics. <b>DIN EN 13300:</b> Contrast ratio: hiding power H <sub>10</sub> -class 2 at a spreading rate of 140 ml/m <sup>2</sup> Wet scrub resistance: R-class 2 Gloss level: G4 dull matt <b>colour:</b> white	approx. 140-170 ml	12.5 l 5 l	24 60
				

## Wet scrub resistance class 3



### Malerweiß

Interior paint with very good hiding power, a very high degree of whiteness and excellent application properties. Free of solvents and harmful emissions. Without the addition of preservatives.

#### DIN EN 13300:

Contrast ratio: hiding power H<sub>10</sub>-class 1 at a spreading rate of 125 ml/m<sup>2</sup>

Wet scrub resistance: R-class 3

Gloss level: G4 dull matt

**colour:** white / off-white



spreading rate / m<sup>2</sup>  
per coating

approx. 150 ml

packaging

bucket/Euro  
pallet

white	white
12.5 l	32
5 l	72
2.5 l	120
off-white	
12.5 l	32



### Trendweiß

Slightly filling dispersion paint for interior use. High whiteness, easy to apply, with good hiding power. Free of solvents and harmful emissions. Without the addition of preservatives.

#### DIN EN 13300:

Contrast ratio: hiding power H<sub>10</sub>-class 1 at a spreading rate of 165 ml/m<sup>2</sup>

Wet scrub resistance: R-class 3

Gloss level: G4 dull matt

**colour:** white / off-white



approx. 150 ml

12.5 l	32
--------	----



### Objektweiß

Field proven paint for interior walls and ceilings, good hiding power and filling properties, easy to apply. Free of solvents and harmful emissions. Without the addition of preservatives.

#### DIN EN 13300:

Contrast ratio: hiding power H<sub>10</sub>-class 1 at a spreading rate of 165 ml/m<sup>2</sup>

Wet scrub resistance: R-class 3

Gloss level: G4 dull matt

**colour:** white / off-white



approx. 150 ml

white	
12.5 l	32
5 l	72
off-white	
12.5 l	32



### Objektweiß *airless*

Airless set, field proven paint for interior walls and ceilings, good hiding power and filling properties, easy to apply. Free of solvents and harmful emissions. Without the addition of preservatives.

#### DIN EN 13300:

Contrast ratio: hiding power H<sub>10</sub>-class 1 at a spreading rate of 165 ml/m<sup>2</sup>

Wet scrub resistance: R-class 3

Gloss level: G4 dull matt

**colour:** white



approx. 150-200 ml

120 l	3
30 l	12
800 l	
Container on request	

## Wet scrub resistance class 3



### Silikat-Innenfarbe

Silicate paint for interior use according to DIN 18363. With good hiding power. Matt and highly diffusible coating for the entire living area. Free of solvents and harmful emissions. Without the addition of preservatives.

#### DIN EN 13300:

Contrast ratio: hiding power  $H_{10}$ -class 2 at a spreading rate of 125 ml/m<sup>2</sup>

Wet scrub resistance: R-class 3

Gloss level: G4 dull matt

**colour:** white / off-white



spreading rate / m<sup>2</sup>  
per coating

approx. 150 ml

packaging

12.5 l  
5 l

bucket/Euro  
pallet

32  
72

off-white  
12.5 l

off-white  
32



### Deckenschwarz

Black paint for interior use, i.e. for suspended ceilings in cinemas, super markets, discotheques, factory halls. Good hiding power and excellent application qualities. Free of solvents and harmful emissions.

#### DIN EN 13300:

Contrast ratio: hiding power  $H_{10}$ -class 1 at a spreading rate of 165 ml/m<sup>2</sup>

Wet scrub resistance: R-class 3

Gloss level: G4 dull matt

**colour:** black



approx. 150 ml

12.5 l

32



### Wand- und Deckenfarbe

Dispersion paint for walls and ceilings. Wipe-resistant, with good hiding power, easy to apply. Free of solvents and harmful emissions.

#### DIN EN 13300:

Contrast ratio: hiding power  $H_{10}$ -class 2 at a spreading rate of 165 ml/m<sup>2</sup>

Wet scrub resistance: R-class 4

Gloss level: G3 matt

**colour:** white



approx. 170 ml

12.5 l










32





Paints for exterior use

		spreading rate / m <sup>2</sup> per coating	packaging	bucket/Euro pallet
	<p><b>Reno-Fassaden-Finish</b></p> <p>Premium quality hybrid facade paint for universal use. Suitable for ETIC systems. Low tendency to attract pollution, thus the facade stays clean longer. Good water vapour diffusion and low water absorption due to a special hybrid binder and modified silicone resin. Slightly filling, low tendency for cracks and low thermoplasticity. Outstanding fine structure, very good hiding power and whiteness combined with excellent application properties. Coating is highly resistant against algae and fungi.</p> <p><b>Colour Resistance according to BFS Data Sheet No. 26:</b> A / group 1 – 3 (depending on colour)</p> <p><b>colour:</b> white</p>	<p>approx. 200 ml</p>	<p>12.5 l 5 l</p>	<p>32 72</p>
	<p><b>Hybrid-Fassadenfarbe</b></p> <p>Light filling hybrid facade paint for universal use based on silicone resin and pure acrylic-dispersion. The material is highly diffusible, driving rain proof and water repellent. Suitable on all mineral undergrounds, silicone-resin and dispersion paints and plasters, also for ETIC systems. Low tendency to attract pollution, thus the facade stays clean longer. Fine structure, very good hiding power combined with very good application properties impresses. Coating is highly resistant against algae and fungi.</p> <p><b>Colour Resistance according to BFS Data Sheet No. 26:</b> A / group 1 – 3 (depending on colour)</p> <p><b>colour:</b> white</p>	<p>approx. 200 ml</p>	<p>12.5 l 5 l</p>	<p>32 72</p>
	<p><b>Silikon-Fassadenfarbe</b></p> <p>Silicone-based facade paint with good hiding power and high diffusion of water vapour and CO<sub>2</sub>. It is tight against driving rain and resistant against microorganisms. Coating is highly resistant against algae and fungi. Weather resistant due to natural water repelling effect.</p> <p><b>Colour Resistance according to BFS Data Sheet No. 26:</b> B / group 1 – 3 (depending on colour)</p> <p><b>colour:</b> white</p>	<p>approx. 200 ml</p>	<p>12.5 l 5 l</p>	<p>32 72</p>
	<p><b>Sil-Fassadenfarbe</b></p> <p>Special facade paint with siloxane, similar to silicate. Low tension, highly diffusible and weatherproof. Especially suitable for mineral plasters. Coating is highly resistant against algae and fungi.</p> <p><b>Colour Resistance according to BFS Data Sheet No. 26:</b> B / group 1 – 3 (depending on colour)</p> <p><b>colour:</b> white</p>	<p>approx. 200 ml</p>	<p>12.5 l 5 l</p>	<p>32 72</p>

		spreading rate / m <sup>2</sup> per coating	packaging	bucket/Euro pallet
	<b>Reinacrylat-Fassadenfarbe</b> High quality facade paint on pure acrylate basis, with preventive protection of concrete. Silk-matt, with very good hiding power and good coverage on structured substrates. Resistant against industrial gases. Protects concrete against CO <sub>2</sub> . Coating is highly resistant against algae and fungi. <b>Colour Resistance according to BFS Data Sheet No. 26:</b> A / group 1 – 3 (depending on colour) <b>colour:</b> white	approx. 150-180 ml	12.5 l 5 l	32 72
	  			
	<b>Fassadenweiß</b> Facade paint with low tension, for universal use. Weatherproof and permeable. With good hiding power and excellent application properties. Without film preservation. <b>Colour Resistance according to BFS Data Sheet No. 26:</b> B / group 1 – 3 (depending on colour) <b>colour:</b> white	approx. 200 ml	12.5 l 5 l 2.5 l	32 72 120
	<b>Sol-Silikat-Fassadenfarbe</b> Matt sol-silicate facade paint according to DIN 18363, for exterior and interior use. High opacity, highly diffusible. Sol-silicate offers outstanding application properties and high durability. Suitable for mineral substrates and for reworking of old, matt dispersions as well as old silicone-resin based paints. Weatherproof. Without the addition of preservatives. On request product in 12.5 l can be supplied with algicide / fungicide effect. <b>Colour Resistance according to BFS Data Sheet No. 26:</b> B / group 1 – 3 (depending on colour) <b>colour:</b> white	approx. 200 ml	12.5 l 5 l	32 72
				
	<b>Silikat-Fassadenfarbe</b> Matt silicate facade paint according to DIN 18363, for exterior and interior use. High opacity, highly diffusible. Good adhesion on mineral substrates. Coating is highly resistant against acidic air pollutants. Without the addition of preservatives. On request product in 12.5 l can be supplied with algicide / fungicide effect. <b>Colour Resistance according to BFS Data Sheet No. 26:</b> B / group 1 – 3 (depending on colour) <b>colour:</b> white	approx. 200 ml	12.5 l 5 l	32 72
				



		spreading rate / m <sup>2</sup> per coating	packaging	bucket/Euro pallet
	<h3>Silikat-Mineral-Finish</h3> <p>White pigmented, decorative and high filling texturing coating based on silicate with good hiding power for exterior and interior use. Can be used as primer, adhesion promoter and preparation for dispersion-silicate binded coatings. Suitable as priming-, intermediate- or final coat. Free of solvents and harmful emissions. Without the addition of preservatives.</p> <p><b>colour:</b> white</p>	approx. 400-500 g	20 kg	32
		  		
	<h3>Porenbetonbeschichtung</h3> <p>Weatherproof coating for aerated concrete according to criteria of DIN 18558 (test certificate available). For exterior and interior use. Low tension, easy to structure. Resistant to saponification and mechanical strain. Coating is highly resistant against algae and fungi.</p> <p><b>colour:</b> white</p>	priming coat approx. 800 g final coat approx. 1.000 g renovation coating approx. 700 g	20 kg	24
		 		
Tinting paints				
	<h3>Allcolor</h3> <p>Full-tone and tinting colour in intense colours, with very good hiding power. Can be used with dispersion paints or paints based on silicone resin or silicate. Available in 27 different colour tones. All colour tones are water-thinnable and can be mixed amongst each other. For exterior and interior use, weatherproof, excellent washability (class 2 according to DIN EN 13300). Check suitability before tinting special paints. Free of solvents and harmful emissions.</p>	approx. 140-200 ml	10 l 2.5 l 750 ml 250 ml	40 120 *10 *10  *per carton
				

	Oxidrot		Karminrot		Umbra
	Terracotta		Bordeaux		Schiefer
	Mandarine		Aquablau		Schwarz
	Cognac		Azur		Blau
	Gold		Ocker		Violett
	Sonnengelb		Oxidbraun		Rot
	Frühlingsgrün		Havanna		Orange
	Oxidgrün		Torf		Gelb
	Tannengrün		Gotikbraun		Grün



# Primers

		spreading rate / m <sup>2</sup> per coating	packaging	bucket/Euro pallet
	<b>Hydro-Haft- &amp; Tiefgrund</b> Special Hydrosol primer with integrated nanoscale siloxane bonds. For exterior and interior use. Perfectly strengthens sanding substrates. Minimizes absorbency. Odourless and resistant against saponification. With high penetration, even on gypsum, stucco or gypsum boards. No barrier build-up. Free of solvents and harmful emissions. Without the addition of preservatives.	approx. 100-150 ml	200 l 10 l 5 l 2.5 l 1 l	2 60 128 200 *12  *per carton
	   			
	<b>Hydro PowerGrip Gel</b> Special Hydrosol primer in the new form of a gel, perfect for rolling and spraying. For consolidating the substrate and for reducing absorbency. Pure acrylic. No barrier build-up due to integrated adhesion agents. Good adhesion on many, even smooth surfaces. Resistant against saponification. For exterior and interior use. Free of solvents and harmful emissions. Without the addition of preservatives.	approx. 120-150 ml	10 l 5 l	32 60
	  			
	<b>WP-Haftgrund</b> White primer without structuring grain, for exterior and interior use. Can be used as primer, adhesion promoter and for strengthening substrates such as gypsum boards. For all subsequent coatings with paints based on dispersion, silicone or silicate. Levels the surface for subsequent coating with paint or wallpaper. Free of solvents and harmful emissions. Without the addition of preservatives. <b>colour:</b> white	approx. 120-150 ml	12.5 l 5 l	32 72
	  			
	<b>Grundierkonzentrat 1:4</b> Colourless priming concentrate for exterior and interior use. Can be diluted with water. Offers good penetration and good strengthening effect. Alkali resistant and highly productive. Free of solvents and harmful emissions. Without the addition of preservatives. For gypsum boards and low absorbing substrates we recommend the use of JONAS Hydro-Haft- & Tiefgrund.	approx. 70-150 ml	10 l 5 l 1 l	60 128 *12  *per carton
	 			
	<b>Acryl-Tiefgrund</b> Colourless primer for exterior and interior use. Odourless and resistant against saponification. Good strengthening effect on absorbing and sanding substrates. Free of solvents and harmful emissions. Without the addition of preservatives.	approx. 150-200 ml	10 l	60
	  			






## o.K. Technologie®

Your sales argument: Waiving all preservatives enables an environmentally friendly manufacturing process for sustainable products and a healthy room climate in every household.

For JONAS, future means the best possible connection of social, ecological and economical aspects. This includes a consequent development regarding the areas of health and environmental awareness.

All interior paints as well as primers and adhesives are produced using the patented combination of raw materials without the use of preservative agents and replace their former counterparts. The excellent quality and product characteristics are maintained nonetheless.

		spreading rate / m <sup>2</sup> per coating	packaging	bucket/Euro pallet
	<b>Silikon-Grundfestiger</b> Silicone-based primer for exterior and interior use, consolidating the substrate for following silicone-based coating. Odourless, with high penetration and high vapour diffusion. Easy to apply. Free of solvents and harmful emissions.	approx. 150-200 ml	10 l	60
				
	<b>Silikat-Grundfestiger</b> Silicated-based dispersion primer with good penetration properties, for exterior and interior use. Can be used for strengthening and levelling of absorbing mineral substrates as well as for diluting silicate paints and silicate plasters. Free of solvents and harmful emissions. Without the addition of preservatives.	approx. 80-200 ml	10 l 5 l 1 l	60 128 *12
	 			*per carton
	<b>Silikat-Mineralgrund fein</b> Silicate-based white, fine structured primer with good hiding power for exterior and interior use. Can be used as primer and adhesion promoter, especially for subsequent coating with silicate-based dispersion paints. Free of solvents and harmful emissions. Without the addition of preservatives. <b>grain size:</b> fine <b>colour:</b> white	approx. 150 ml	12.5 l 5 l	32 72
	 			
	<b>Silikat-Mineralgrund grob</b> Silicate-based white, coarse structured primer with good hiding power for exterior and interior use. Can be used as primer and adhesion promoter, especially for subsequent coating with silicate-based dispersion paints. Free of solvents and harmful emissions. Without the addition of preservatives. <b>grain size:</b> coarse <b>colour:</b> white	approx. 250-300 ml	12.5 l 5 l	32 72
	 			



		spreading rate / m <sup>2</sup> per coating	packaging	bucket/Euro pallet
	<b>Silikat-Mineral-Finish</b> White pigmented, decorative and high filling texturing coating based on silicate with good hiding power for exterior and interior use. Can be used as primer, adhesion promoter and preparation for dispersion-silicate binded coatings. Suitable as priming-, intermediate- or final coat. Free of solvents and harmful emissions. Without the addition of preservatives. <b>colour:</b> white	approx. 400-500 g	20 kg	32
		  		
	<b>Rissgrund compact</b> Filling and structuring prime coating for fine, net and shrinkage cracks. Rissgrund compact contains fibres for good filling and stability. Increases adhesion on smooth undergrounds. Diffusible, tension-free and alkaline resistant. For universal use: for following coatings with dispersion paints, silicate and silicone resin paints. For exterior and interior use. <b>colour:</b> white	approx. 600-800 g	20 kg 8 kg	32 72
	<b>Iso-Grund</b> Water-based isolating primer, mild smell, for interior and exterior use. White, tension-free. Very good isolating performance against nicotine, soot and water stains, as well as lignin residues on gypsum board. Also isolating stains of tar and bitumen. Excellent adhesion on substrates such as wood, old coatings, glass, non-ferrous metals, prime-coated iron or steel, tiles, plastics (test first). For subsequent coating you can use dispersion paints. <b>colour:</b> white	approx. 100 ml	12.5 l 5 l	32 72
	<b>Tapetengrund</b> White primer for interior use. Ready-to-use, preparing the substrate for subsequent application of fleece wallpapers or other translucent wallpapers. Harmonizes colour differences and levels the absorbency of the underground. Very good adhesion of following wallpaper. Free of solvents and harmful emissions. <b>colour:</b> white	approx. 100-130 ml	10 l 5 l 2.5 l	40 72 120
				
	<b>Tapeziervorstreichfarbe</b> Ready-to-use basic paint as mist coat for wallpapers and wall coverings. Free of solvents and harmful emissions. <b>colour:</b> white	approx. 130-170 g	20 kg	32
				



Primer	Underground											
	concrete outside	concrete inside	dispersion binded paints and plasters	silicone resin paints and plasters	silicate paints and plasters	lime paints and plasters	lime-cement plaster and cement-plaster	gypsum plaster	lime-sandstone	aerated concrete	gypsum board	wood chip board
Hydro-Haft- & Tiefgrund	✓	✓	✓	✓	✓	—	✓	✓	✓	✓	✓	—
Hydro PowerGrip Gel	✓	✓	✓	✓	✓	—	✓	—	✓	—	✓	—
WP-Haftgrund	✓	✓	✓	✓	✓	—	✓	—	✓	—	✓	—
Grundierkonzentrat 1:4	✓	✓	✓	✓	✓	—	✓	—	✓	✓	—	—
Acryl-Tiefgrund	✓	✓	✓	✓	✓	—	✓	—	✓	—	—	—
Silikon-Grundfestiger	✓	✓	✓	✓	✓	○	✓	—	✓	✓	—	—
Silikat-Grundfestiger	—	✓	—	—	✓	○	✓	—	✓	—	—	—
Silikat-Mineralgrund	✓	✓	✓	✓	✓	○	✓	—	✓	—	✓	—
Rissgrund compact	✓	✓	✓	✓	✓	—	✓	—	✓	—	✓	—
Iso-Grund	✓	✓	✓	✓	✓	—	✓	—	—	—	✓	✓
Tapetengrund	✓	✓	✓	✓	✓	—	✓	—	✓	—	✓	—

Primer	Characteristics								
	for inside	for outside	pigmented	penetration	regulating absorbency	underground consolidation	promoting adhesion	isolating stains	filling crack
Hydro-Haft- & Tiefgrund	✓	✓	—	***	***	***	✓	—	—
Hydro PowerGrip Gel	✓	✓	—	*	***	**	✓	—	—
WP-Haftgrund	✓	✓	✓	*	***	*	✓	—	—
Grundierkonzentrat 1:4	✓	✓	—	**	***	***	—	—	—
Acryl-Tiefgrund	✓	✓	—	*	***	**	—	—	—
Silikon-Grundfestiger	✓	✓	—	***	***	***	—	—	—
Silikat-Grundfestiger	✓	✓	—	***	***	***	—	—	—
Silikat-Mineralgrund	✓	✓	✓	—	—	—	✓	—	✓
Rissgrund compact	✓	✓	✓	—	—	—	—	—	✓
Iso-Grund	✓	—	✓	—	—	—	—	✓	—
Tapetengrund	✓	—	✓	—	**	—	—	—	—

## Legend:

- \*\*\* very good
- \*\* good
- \* limited
- ✓ suitable
- test for suitability
- not suitable



Glue for wallpapers

		spreading rate / m <sup>2</sup> per coating	packaging	bucket/Euro pallet
	<b>Vlieskleber</b> Special dispersion-based glue for interior use, ready-to-use. Suitable for technical glass-fleece or cellulose-fleece (with or without pigments) which will be painted over. Outstanding quick and smooth application combined with a very even spreading. Free of solvents and harmful emissions. Without the addition of preservatives.	approx. 150-250 g    	16 kg	32
	<b>Gewebekleber</b> Strong dispersion-based glue for interior use. Ready-to-use. Suitable for glass fleece (with or without pigments) which will be painted over and for heavy glass fabrics. Outstanding quick and smooth application combined with a very high adhesion. Free of solvents and harmful emissions. Without the addition of preservatives.	approx. 300-400 g    	16 kg	32
	<b>Rauhfaserkleber</b> Special glue for woodchip wallpaper and Vlies-Rauhfaser on interior surfaces. Ready-to-use. Suitable for application by brush, roller, pasting machine, airless-spraying and wall-pasting technique. Free of solvents and harmful emissions. Without the addition of preservatives.	approx. 200-250 g    	16 kg	32



Texturing coatings

		spreading rate / m <sup>2</sup> per coating	packaging	bucket/Euro pallet
	<b>Streichputz fein</b> High quality brush-on plaster with fine structure dispersion based for exterior and interior use. Can be used as priming coat for following applications of plasters with organic binders. Free of solvents and harmful emissions. <b>grain size:</b> fine <b>colour:</b> white	approx. 300-350 g	20 kg 8 kg	32 72
	 			
	<b>Streichputz grob</b> High quality brush-on plaster with coarse structure dispersion based for exterior and interior use. Can be used as priming coat for following applications of plasters with organic binders. Free of solvents and harmful emissions. <b>grain size:</b> coarse <b>colour:</b> white	approx. 400-500 g	20 kg 8 kg	32 72
	 			
	<b>Silikon-Streichputz</b> Silicone-based brush-on plaster. Filling, with good hiding power. With water repellent properties. Priming coat for following applications with silicone paints or silicone stucco. Weatherproof. Free of solvents and harmful emissions. Free of solvents and harmful emissions. <b>grain size:</b> fine <b>colour:</b> white	approx. 300-350 g	20 kg	32
				
	<b>Silikat-Mineral-Finish</b> White pigmented, decorative and high filling texturing coating based on silicate with good hiding power for exterior and interior use. Can be used as primer, adhesion promoter and preparation for dispersion-silicate binded coatings. Suitable as priming-, intermediate- or final coat. Free of solvents and harmful emissions. Without the addition of preservatives. <b>colour:</b> white	approx. 400-500 g	20 kg	32
	  			
	<b>Silikat-Streichputz</b> Silicate-based brush-on plaster for exterior and interior use, with good filling properties and good hiding power. Priming coat for following applications with silicate paints or silicate stucco. Free of solvents and harmful emissions. <b>grain size:</b> fine <b>colour:</b> white	approx. 300-350 g	20 kg	32
	 			







## Sustainability

The responsible utilization of natural resources on an ecological, economical as well as a social level is part of our philosophy.

As the leading manufacturer of private label interior and exterior paints in Europe, we set our focus on health-conscious products since the 1980's. With success: 40 years ago, we started the conversion from solvent- to water-based products, later followed by the development of our emission- as well as solvent-free premium product line (ELF).

Today, we produce interior paints exclusively without the use of preservative agents and utilize environmentally friendly recycle packaging. With these qualities, we set new standards for sustainable construction paints.



		spreading rate / m <sup>2</sup> per coating	packaging	bucket/Euro pallet
	<b>Spray Finish <i>soft grain</i> mittel</b> Texturing spray coating for interior use with medium texture. The material can be applied fast and efficiently. Low loss of material thanks to easy and safe handling when spraying. Very good hiding power, high resistance to mechanical damage and high diffusivity. Perfect binding of the texturing agents. Formation of clear edges. Suitable as substrate for glazing techniques. Free from fogging active substances. Free of solvents and harmful emissions. Without the addition of preservatives. <b>colour:</b> white	approx. 800-950 g	20 kg	24
				
	<b>Renoplast</b> Silk gloss plastic for interior use, easy to model. Free of solvents and harmful emissions. Without the addition of preservatives. <b>DIN EN 13300:</b> contrast ratio: hiding power H <sub>10</sub> -class 1 at a spreading rate of 165 ml/m <sup>2</sup> wet scrub resistance: R-class 2 gloss level: G2b medium glos <b>colour:</b> white	approx. 500-1000 g	20 kg	24
				



MIX products

Paints for interior use		Packaging Base 1	Packaging Base 3
	<b>Doppeldecker</b> High quality single-coat paint for interior use with matt finish. Doppeldecker is characterized by excellent application properties. Long open time increase the security of the processing properties. The product conserves the structure and gives a durable surface. Free of solvents and harmful emissions. Wet scrub resistance: R-class 2 acc. to DIN EN 13300 Tinting may lead to variations in the technical data.	 12.5 l 5 l 2.5 l 1.25 l	11.9 l 4,75 l 2.4 l 1.2 l
	<b>Samtmatt premium</b> Premium quality hard-wearing silk-matt latex paint for interior use. Enhances the writing resistance (finish), especially for dark colours. Good hiding power as well as a very fine and even structure combined with excellent application properties guarantee an perfect surface. Free of solvents and harmful emissions. Wet scrub resistance: R-class 1 acc. to DIN EN 13300 Tinting may lead to variations in the technical data.	 12.5 l 5 l 2.5 l 1.25 l	11.9 l 4,75 l 2.4 l 1.2 l
	<b>Seidenglanz premium</b> Premium quality silk-gloss latex paint for exterior and interior use. Retaining the structure and hard-wearing. UV-resistant with stable gloss. Resistant to disinfectants. Weatherproof. Free of solvents and harmful emissions. Wet scrub resistance: R-class 1 acc. to DIN EN 13300 Tinting may lead to variations in the technical data.	 12.5 l 5 l 2.5 l 1.25 l	11.9 l 4,75 l 2.4 l 1.2 l
	<b>Seidenlatex</b> Silk-gloss latex paint of high quality, for exterior and interior use. Good surface finish with accentuating effects on structured wall-papers or glass fibres. UV-resistant with stable gloss. Good hiding power, low smell and environmentally friendly. Resistent to disinfectants. Free of solvents and harmful emissions. Wet scrub resistance: R-class 1 acc. to DIN EN 13300 Tinting may lead to variations in the technical data.	 12.5 l 5 l 2.5 l 1.25 l	11.9 l 4,75 l 2.4 l 1.2 l
	<b>Sol-Silikat-Innenfarbe</b> Highly diffusible silicate paint for interior use with very good hiding power. Sol-silicate offers outstanding processing properties and high durability. Suitable for mineral substrates and for reworking old, matt dispersion and silicone-resin based paints. Free of plasticizers and fogging active substances. Free of solvents and harmful emissions. Wet scrub resistance: R-class 2 acc. to DIN EN 13300 Tinting may lead to variations in the technical data.	 12.5 l 5 l 2.5 l 1.25 l	11.9 l 4,75 l 2.4 l 1.2 l

Paints for interior use		Packaging Base 1	Packaging Base 3
	<b>Dura-In</b> Premium quality paint for interior use, especially for surfaces which are under high mechanical stress. Any writing effects can be removed easily and the paint has a low tendency for soiling. It offers good hiding power, together with the very fine and even texture this guarantees a perfect surface. A long open time and excellent application properties make it easy to use. Resistant to disinfectants. Free of solvents and harmful emissions. Wet scrub resistance: R-class 1 acc. to DIN EN 13300 Tinting may lead to variations in the technical data.	12.5 l 5 l 2.5 l 1.25 l	11.9 l 4.75 l 2.4 l 1.2 l
	<b>First Class</b> Single coat paint with very good hiding power and a very fine surface finish. For luxurios matt and smooth surfaces. Particularily suitable for adverse lighting conditions (such as indirect light reflections). With excellent application properties and long open time. Low consumption and good ability to conserve the structure of the substrate. Free of solvents and harmful emissions. Wet scrub resistance: R-class 2 acc. to DIN EN 13300 Tinting may lead to variations in the technical data.	12.5 l 5 l 2.5 l 1.25 l	11.9 l 4.75 l 2.4 l 1.2 l
	<b>Bio-Innensilikat</b> Silicate paint for interior use, highly diffusible and high hiding power. With high durability. Free of plasticizers and fogging-active substances. Free of solvents and harmful emissions. Wet scrub resistance: R-class 2 acc. to DIN EN 13300 Tinting may lead to variations in the technical data.	12.5 l 5 l 2.5 l 1.25 l	11.9 l 4.75 l 2.4 l 1.2 l
	<b>Iso-Matt-Aqua</b> Water-based isolating paint for interior use, no smell. Matt and tension-free, for isolating nicotine, soot and dried water stains. Free of solvents and harmful emissions. Wet scrub resistance: R-class 2 acc. to DIN EN 13300 Can be tinted out of white Tinting may lead to variations in the technical data.	12.5 l 5 l	
	<b>Malerweiß</b> Interior paint with very good hiding power and excellent application properties. Suitable for residential living with high prentention. Free of solvents and harmful emissions. Wet scrub resistance: R-class 3 acc. to DIN EN 13300 Tinting may lead to variations in the technical data.	12.5 l 5 l 2.5 l 1.25 l	11.9 l 4.75 l 2.4 l 1.2 l

Paints for interior use		Packaging Base 1	Packaging Base 3
	<b>Trendweiß</b> Slightly filling dispersion paint for interior use. Easy to apply, with good hiding power. Free of solvents and harmful emissions. Wet scrub resistance: R-class 3 acc. to DIN EN 13300 Tinting may lead to variations in the technical data.		12.5 l 5 l 2.5 l 1.25 l
			11.9 l 4.75 l 2.4 l 1.2 l
	<b>Silikat-Innenfarbe</b> Silicate paint for interior use. With good hiding power. Matt and highly diffusible coating for the entire living area. Free of solvents and harmful emissions. Wet scrub resistance: R-class 3 acc. to DIN EN 13300 Tinting may lead to variations in the technical data.		12.5 l 5 l 2.5 l 1.25 l
			11.9 l 4.75 l 2.4 l 1.2 l
Paints for exterior use		Packaging Base 1	Packaging Base 3
	<b>Reno-Fassaden-Finish</b> Premium quality hybrid facade paint for universal use. Suitable for ETIC systems. Low tendency to attract pollution, thus the facade stays clean longer. Good water vapour diffusion and low water absorption due to a special hybrid binder and modified silicone resin. Slightly filling, low tendency for cracks and low thermoplasticity. Outstanding fine structure, very good hiding power and whiteness combined with excellent application properties. Coating is highly resistant against algae and fungi. <b>Colour Resistance according to BFS Data Sheet No. 26:</b> A / group 1 – 3 (depending on colour) Tinting may lead to variations in the technical data.		12.5 l 5 l 2.5 l 1.25 l
			11.9 l 4.75 l 2.4 l 1.2 l
	<b>Hybrid-Fassadenfarbe</b> Light filling hybrid facade paint for universal use based on silicone resin and pure acrylic-dispersion. The material is highly diffusible, driving rain proof and water repellent. Suitable on all mineral undergrounds, silicone-resin and dispersion paints and plasters, also for ETIC systems. Low tendency to attract pollution, thus the facade stays clean longer. Fine structure, very good hiding power combined with very good application properties impresses. Coating is highly resistant against algae and fungi. <b>Colour Resistance according to BFS Data Sheet No. 26:</b> A / group 1 – 3 (depending on colour) Tinting may lead to variations in the technical data.		12.5 l 5 l 2.5 l 1.25 l
			11.9 l 4.75 l 2.4 l 1.2 l



Paints for exterior use		Packaging Base 1	Packaging Base 3
	<b>Silikon-Fassadenfarbe</b> Silicone-based facade paint with good hiding power and high diffusion of water vapour and CO <sub>2</sub> . It is tight against driving rain and resistant against microorganisms. Coating is highly resistant against algae and fungi. Weather resistant due to natural water repelling effect. <b>Colour Resistance according to BFS Data Sheet No. 26:</b> B / group 1 – 3 (depending on colour) Tinting may lead to variations in the technical data.	12.5 l 5 l 2.5 l 1.25 l	11.9 l 4.75 l 2.4 l 1.2 l
			
	<b>Sil-Fassadenfarbe</b> Special facade paint with siloxane, similar to silicate. Low tension, highly diffusible and weatherproof. Especially suitable for mineral plasters. Coating is highly resistant against algae and fungi. <b>Colour Resistance according to BFS Data Sheet No. 26:</b> B / group 1 – 3 (depending on colour) Tinting may lead to variations in the technical data.	12.5 l 5 l 2.5 l 1.25 l	11.9 l 4.75 l 2.4 l 1.2 l
			
	<b>Reinacrylat-Fassadenfarbe</b> High quality facade paint on pure acrylate basis, with preventive protection of concrete. Silk-matt, with very good hiding power and good coverage on structured substrates. Resistant against industrial gases. Protects concrete against CO <sub>2</sub> . Coating is highly resistant against algae and fungi. <b>Colour Resistance according to BFS Data Sheet No. 26:</b> A / group 1 – 3 (depending on colour) Tinting may lead to variations in the technical data.	12.5 l 5 l 2.5 l 1.25 l	11.9 l 4.75 l 2.4 l 1.2 l
			
	<b>Sol-Silikat-Fassadenfarbe</b> Matt sol-silicate paint for exterior use with good hiding power. Highly diffusible. Sol-silicate offers outstanding application properties and high durability. Suitable for mineral substrates and for reworking of old, matt and sustainable dispersions as well as old silicone-resin based paints. Weatherproof. <b>Colour Resistance according to BFS Data Sheet No. 26:</b> B / group 1 – 3 (depending on colour) Tinting may lead to variations in the technical data.	12.5 l 5 l 2.5 l 1.25 l	11.9 l 4.75 l 2.4 l 1.2 l
	<b>Silikat-Fassadenfarbe</b> Matt silicate paint for exterior use. High opacity, highly diffusible. Good adhesion on mineral substrates. Coating is highly resistant against acidic air pollutants. <b>Colour Resistance according to BFS Data Sheet No. 26:</b> B / group 1 – 3 (depending on colour) Tinting may lead to variations in the technical data.	12.5 l 5 l 2.5 l 1.25 l	11.9 l 4.75 l 2.4 l 1.2 l



## Primer

packaging



### WP-Haftgrund

White primer without structuring grain, for exterior and interior use. Can be used as primer, adhesion promoter and for strengthening substrates such as gypsum boards. For all subsequent coatings with paints based on dispersion, silicone or silicate. Levels the surface for subsequent coating with paint or wallpaper. Free of solvents and harmful emissions. Without the addition of preservatives.

Can be tinted in light and medium shades using the JONAS MIX-System. All colours are only approximately feasible.

Tinting may lead to variations in the technical data.

12.5 l  
5 l



## Texturing coating

packaging



### Silikat-Mineral-Finish

White pigmented, decorative and high filling texturing coating based on silicate with good hiding power for exterior and interior use. Can be used as primer, adhesion promoter and preparation for dispersion-silicate binded coatings. Suitable as priming-, intermediate- or final coat. Free of solvents and harmful emissions. Without the addition of preservatives.

Can be tinted out of white

Tinting may lead to variations in the technical data.

20 kg



### Spray Finish *soft grain mittel*

Texturing spray coating for interior use with medium texture. The material can be applied fast and efficiently. Low loss of material thanks to easy and safe handling when spraying. Very good hiding power, high resistance to mechanical damage and high diffusivity. Perfect binding of the texturing agents. Formation of clear edges. Suitable as substrate for glazing techniques. Free from fogging active substances. Free of solvents and harmful emissions. Without the addition of preservatives.

Can be tinted out of white

Tinting may lead to variations in the technical data.

20 kg



34

35



## **o.K. Technologie® (free of preservatives)**

For JONAS, future means the best possible connection of social, ecological and economical aspects. This includes a consequent development regarding the areas of health and environmental awareness. For this reason, all interior paints as well as primers and adhesives are produced without the use of preservative agents and replace their former counterparts. The excellent quality and product characteristics are maintained nonetheless.



## **The European environmental sign – EU Ecolabel**

Since 1992, the EU Ecolabel serves as international environmental seal of quality that marks a uniform provision for eco-friendly products and services. The award is assigned for products and services that have lower environmental effects than comparable counterparts. The EU Ecolabel should help end-consumers identify eco-friendly and healthy products.



## **DGNB - sustainable construction**

We are member of Europe's largest network for sustainable construction, the 'Deutsche Gesellschaft für nachhaltiges Bauen e.V.' (DGNB). The DGNB certifies construction projects, which are specifically energy efficient and sustainable. Many JONAS products are DGNB certified and listed in the DGNB navigator. The DGNB technical data sheets list extensive details regarding the sustainability of our products.



## **TÜV SÜD „Low emissions, checked for harmful substances and monitored production“**

Testing and certification of dispersion paints according to the quality standards of TÜV SÜD (Technical Inspectorate for Southern Germany): low emissions, tested for hazardous substances and monitored production process.

The TÜV SÜD Industrie Service GmbH tests and certifies according to the test and certification regulations for product tests. To get the award for the products, tests are made on selected samples, the production plant is inspected and compliance to the regulations is verified. Test standard TM-07 „dispersion paints“.



## **The Blue Angel**

The Blue Angel is an environmental label for products and services which are particularly environmentally friendly. It was established in Germany in 1978. If you use products or services awarded with the environmental label The Blue Angel, you can be sure to help yourself, the environment and the future. The Blue Angel is the federal environmental sign for protecting human life and the environment. It is ambitious, independent and has proved as guideline for environmentally friendly products for more than 40 years. JONAS products are certified according to DE-UZ102 (Version 2019) for low-emission.



## EPD = environmental product declaration

(according to ISO 14025)

Sustainability gets more and more important, also in the field of construction work. It is seen positively with respect to environment / environmental protection. EPDs are based on the EU directive for construction products and provide the data base for an ecological evaluation of buildings. With the help of various parameters EPDs allow a theoretical calculation of the sustainability of individual products.

Initiator of the EPDs is the Institut Bauen und Umwelt e.V. (IBU), an initiative of construction product manufacturers, who decided to approach the demand for more sustainability at construction sites. With only few exceptions EPDs are available for all JONAS products.



## Disinfectant resistance

PILF: Test of paints with respect to resistance against disinfectants. The durability of coatings against disinfectants is tested, concentrating on disinfectants which are used in hospitals and surgeries for surface disinfection.



## CE-Labeling


Quality standard for exterior and interior plasters with organic binders. To be labelled according to EN 15824 for exterior and interior plasters with organic binders, fire behaviour and adhesive strength are tested. According to the German regulation for building products the CE label is mandatory for all exterior and interior plasters since 2011.



## TU Technical University Dortmund





















Diffusion behaviour and water absorption

Test of coatings with respect to diffusion behaviour against CO<sub>2</sub> and H<sub>2</sub>O and with respect to water absorption, both important parameters for a healthy living climate.





## We use the following pictograms for our JONAS products

	Application outside and inside	<b>Nassabrieb Klasse</b> <b>1</b>	Wet scrub resistance: class 1		Add a maximum of 5% water
	Application only outside	<b>Nassabrieb Klasse</b> <b>2</b>	Wet scrub resistance: class 2		Stir
	Application only inside	<b>Nassabrieb Klasse</b> <b>3</b>	Wet scrub resistance: class 3		Shake
	Brush	<b>Nassabrieb Klasse</b> <b>4</b>	Wet scrub resistance: class 4		Clean with water
	Roll	<b>Deckkraft Klasse</b> <b>1</b> bei 8 m <sup>2</sup> /l	Contrast ratio: hiding power class 1 at a spreading rate of 125 ml/m <sup>2</sup>		Clean with solvent
	Application with brush	<b>Deckkraft Klasse</b> <b>1</b> bei 7 m <sup>2</sup> /l	Contrast ratio: hiding power class 1 at a spreading rate of 140 ml/m <sup>2</sup>		Minimum application temperature +5°C
	Application with trowel	<b>Deckkraft Klasse</b> <b>1</b> bei 6 m <sup>2</sup> /l	Contrast ratio: hiding power class 1 at a spreading rate of 165 ml/m <sup>2</sup>		Minimum application temperature +0°C
	Application with pasting machine	<b>Deckkraft Klasse</b> <b>2</b> bei 8 m <sup>2</sup> /l	Contrast ratio: hiding power class 2 at a spreading rate of 125 ml/m <sup>2</sup>		Store cool, but not freezing
	Spray (airless)	<b>Deckkraft Klasse</b> <b>2</b> bei 7 m <sup>2</sup> /l	Contrast ratio: hiding power class 2 at a spreading rate of 140 ml/m <sup>2</sup>		Pay attention to the technical data sheet
 Trichterpistole	Spray with hopper gun or similar	<b>Deckkraft Klasse</b> <b>2</b> bei 6 m <sup>2</sup> /l	Contrast ratio: hiding power class 2 at a spreading rate of 165 ml/m <sup>2</sup>		Also available as a tinting base
<b>ELF</b>	Free of solvents and harmful emissions				
<b>A&amp;F</b>	Film protection against algae - fungi				

JONAS products	nozzle size in Inch	Storch filter	Wagner filter	Graco filter
<b>Paints for interior use</b>				
Bio-Innensilikat	0,021 - 0,025	remove filter	filter green 30 mesh	filter black 30 mesh
Deckenschwarz	0,019 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Doppeldecker	0,019 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Dura-In	0,019 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
First Class	0,019 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Hochglanz <i>premium</i>	0,017 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Iso-Matt-Aqua	0,019 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Malerweiß	0, 019 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Malerweiß extra	0,019 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Mattlatex	0,019 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Objektweiß	0,019 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Objektweiß airless	0,019 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Rapidweiß	0,019 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Samtmatt <i>premium</i>	0,017 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Seidenglanz <i>premium</i>	0,017 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Seidenlatex	0,017 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Silikat-Innenfarbe	0,021 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Silikon Innenfarbe	0,019 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Sol-Silikat-Innenfarbe	0,021 - 0,025	remove filter	filter green 30 mesh	filter black 30 mesh
Trendweiß	0,019 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Ultramatt <i>premium</i>	0,017 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
<b>Paints for exterior use</b>				
Fassadenweiß	0,021 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Hybrid-Fassadenfarbe	0,021 - 0,027	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Reinacrylat-Fassadenfarbe	0,021 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Sil-Fassadenfarbe	0,021 - 0,027	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Silikat-Fassadenfarbe	0,021 - 0,027	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Silikon-Fassadenfarbe	0,021 - 0,027	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Sol-Silikat-Fassadenfarbe	0,021 - 0,027	remove filter	filter green 30 mesh	filter black 30 mesh
<b>Primers</b>				
Hydro PowerGrip Gel	0,017 - 0,021	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Iso-Grund	0,021 - 0,027	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Tapetengrund	0,019 - 0,025	filter white 60 mesh	filter green 30 mesh	filter black 30 mesh
WP-Haftgrund	0,017 - 0,021	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
<b>Glue for wallpapers</b>				
Gewebekleber (150-200 bar)	0,021 - 0,027	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Rauhfaserleber	0,021 - 0,027	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh
Vlieskleber (150-200 bar)	0,021 - 0,025	filter white 60 mesh	filter white 50 mesh	filter blue 60 mesh



JONAS Farben GmbH  
Dieselstraße 42-44 · 42489 Wülfrath  
Telefon +49 (0) 20 58-789-0  
Fax +49 (0) 20 58-789-55



[www.jonas-farben.de](http://www.jonas-farben.de)